

R. T. Vanderbilt Company, Inc.'s Paint Department supplies many raw materials which are extensively used in the paint and coatings industries. This folder provides general information on these products. Samples and literature providing technical information are available on request.

Mineral Products/Silicate Extender Pigments

Industrial Talc – Hydrous Magnesium Silicate

NYTAL® industrial talc is supplied in a number of grades that meet a wide range of fineness and binder requirements. Its high brightness, chemical inertness, easy “stir-in” dispersion and excellent suspension qualities combine to give the paint chemist a truly versatile pigment with which to formulate both solvent and waterborne coatings. The fineness of each grade follows:

	Screen residue (+325 mesh)	Hegman Fineness
NYTAL 200	2.50%	0-1
NYTAL 300	0.08%	4
NYTAL 400	trace	5
NYTAL 3300	0.1%	4
NYTAL 6600	trace	6
NYTAL 7700	trace	7
NYTAL 3X	2.50%	0-1
NYTAL 5X	1.00%	2

NYTAL 3300, 6600 and **7700** are talcs with tightly controlled particle size distribution for applications in low VOC coatings. **NYTAL 3300** yields a lower viscosity than **NYTAL 300** and can be used in low VOC and other coatings where the chemical inertness and suspension properties of talc are desirable. **NYTAL 6600** and **NYTAL 7700** are ultra fine, low viscosity talcs that can be used as extenders for prime pigments in high performance coatings. **NYTAL** industrial talcs are not currently available in the EU.

VANTALC® mineral filler is a high purity, platy talc (magnesium silicate) that is effective for the gloss control of coatings. The properties of **VANTALC** grades are as follows:

	Hegman Fineness	Dry Brightness	Oil Absorption
VANTALC 6H	6	88	52
VANTALC 6H-II	6	91	55
VANTALC F2003	5	86	45
VANTALC F2504	5	89	42

Wollastonite – Calcium Metasilicate

VANSIL® wollastonite is a high brightness mineral filler and functional extender pigment for paint. **VANSIL** has a relatively high pH (10-11) that maintains the pH of latex paints in the desired range. It has low binder demand and low water solubility. The fineness of each grade follows:

	Screen Residue	Hegman Fineness
VANSIL WG	20.0% +200 mesh	0
VANSIL HR-2000	10.0% +200 mesh	0
VANSIL HR-1500	5.0% +200 mesh	0
VANSIL HR-325	0.05% +325 mesh	4
VANSIL W-10	4.5% +200 mesh	0
VANSIL W-20	3.0% +325 mesh	0-1
VANSIL W-30	0.09% +325 mesh	4
VANSIL W-40	0.1% +325 mesh	5
VANSIL W-50	0.05% +400 mesh	6+

VANCOTE® wollastonite is a **VANSIL** grade with either an amino or epoxy silane treatment to improve the adhesion of coatings and corrosion resistance. Standard grades are **VANCOTE W40AS, W50AS** and **W50ES**. Other grades can be produced for special requirements.

Clay (Kaolin) – Hydrous Aluminum Silicate

PEERLESS®, **DIXIE CLAY**® and **BILT-PLATES**® 156 fillers are air-floated clays available in grades that vary in brightness and fineness. They are used in coatings, primers, crack fillers and caulking compounds when high brightness is not a prerequisite. The fineness of each grade follows:

	Screen Residue
PEERLESS 1	0.40% +200 mesh
PEERLESS 3	0.40% +200 mesh
DIXIE CLAY	0.20% +325 mesh
BILT-PLATES 156	0.05% +325 mesh

Pyrophyllite – Hydrous Aluminum Silicate

PYRAX® pyrophyllite is useful as an extender pigment when a relatively coarse material is required. Its micaceous structure helps to control the mud cracking of texture paints. The fineness of each grade follows:

	Screen Residue (+200 mesh)
PYRAX B	1.0%
PYRAX WA	3.0%
VEECOTE ®	0.3%

Inorganic Thixotropes for Aqueous Systems

VAN GEL® **B** and **VEEGUM**® **T** smectite clays (magnesium aluminum silicate) are specially formulated for easy incorporation and consistent performance in aqueous systems. Aqueous dispersions of **VAN GEL B** or **VEEGUM T** are highly thixotropic gels at low solids, and are resistant to bacterial and enzymatic degradation. The use of **VAN GEL B** or **VEEGUM T** in a coating formula results in a product with no separation and with uniform thixotropic consistency that requires no stirring, while promoting good flow and brushing characteristics. The result is “dripleless” application and leveling without sag. **VAN GEL B** or **VEEGUM T**, in combination with an associative thickener, has minimal effect on the gloss of semi-gloss latex paints.

Additives

Drier Accelerators and Stabilizers

ACTIV-8® and **ACTIV-8 HGL** drier accelerators are used to optimize drier performance in a wide range of coatings. The active ingredient is 1,10-phenanthroline, offered in different solvent blends. The solutions perform well with manganese and/or cobalt driers in solvent- and waterborne coatings. 1,10-phenanthroline Technical Grade is also available.

A “How-to” Guide for the Use of **ACTIV-8** is available on request.

Corrosion Inhibitors

VANCOR® corrosion inhibitors are metallic sulfonates in solvents that are not on the HAPS list. Calcium and barium sulfonates are available. Salt-spray tests have shown that these products improve the corrosion resistance of coatings. The **VANCORs** perform well in water-reducible alkyd and latex coatings. **VANCOR 081** (barium sulfonate) also acts as a flash rust inhibitor.

Flow Control Agent for Solvent-Borne Paints

RHEOTOL® paint additive is a stable nonreactive film-forming organic composition. Useful in solvent-borne coatings, **RHEOTOL** performs as a mixing and dispersing aid in many types of paint, particularly those based on poor wetting vehicles. It assists pigment wetting and dispersion, improves flow, leveling and gloss, and increases paste flow, allowing a higher percentage of pigment to be mixed in a given amount of vehicle.

Organic Thickeners for Aqueous Systems

VANZAN® anionic polysaccharide (xanthan gum) is produced from the fermentation of carbohydrates by the microorganism *xanthomomas campestris*. It is supplied as a creamy-white powder that forms pseudoplastic colloidal solutions in water and is insoluble in most organic liquids. **VANZAN** has exceptional thickening, suspending and stabilizing properties in the presence of acids, bases and salts, and at elevated temperatures. The grades used in coating applications are **VANZAN** and **VANZAN D**.

Dispersing Agents for Aqueous Systems

DARVAN® surfactants are anionic dispersing agents. They disperse finely divided solids in water and help to keep them dispersed. The following **DARVAN** products are useful in the formulation of paints and coatings:

DARVAN 1 (SD) is a general purpose dispersing agent. It is a granular product composed of sodium salts of polymerized alkyl naphthalene sulfonic acid. It increases paste flow, allowing a higher percentage of pigment to be mixed in a given amount of vehicle.

DARVAN 7-N is a polyelectrolyte dispersing agent in an aqueous solution. It is a minimum foaming dispersing agent.

DARVAN 670 is a general purpose dispersing agent, sodium salts of polymerized naphthalene sulfonates.

DARVAN 811 is a sodium polyacrylate solution for high solids mineral slurries such as kaolin, calcium carbonate, etc.

Mold Inhibitors

VANCIDE® 89 inhibitor is effective in all solvent-borne paints. It complies with USDA requirements for use in paints applied to the walls and ceilings of federally inspected meat packing establishments.

VANCIDE MZ-96 is a very effective heat stable mold inhibiting powder for use in unmodified latex paints, joint compounds, adhesives and textured finishes.

Preservative

VANCIDE TH preservative is effective for latex paints. It prevents attack by microorganisms while the paint is in storage. It is completely soluble in water, and can therefore be added at any point during manufacture.

Synthetic Rubber Polymers

NEOPRENE

Available as an emulsion in many grades for various applications. Uses include industrial and decorative coatings, dipped goods, saturants and wet end additives for fibrous products.

HYPALON®

Available in various grades that are solvent-soluble. Films are flexible and extensible at low temperature, and are resistant to oils and solvents.

HYPALON is a registered trademark of DuPont Performance Elastomers, LLC.

Please contact R.T. Vanderbilt Company, Inc. for further information on the products described in this folder. Samples and Technical Data Sheets are available on request.

R.T. Vanderbilt Company, Inc.
Paint Department
30 Winfield Street
Norwalk, CT 06855
(203) 853-1400
FAX: (203) 853-1452
E-mail: paint@rtvanderbilt.com
Website: www.rtvanderbilt.com

Before using, read, understand and comply with the information and precautions in the Material Safety Data Sheet, label and other product literature. The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all-inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a specific purpose and for adopting such safety precautions as may be required. R.T. Vanderbilt Company, Inc. does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling or further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent, trademark or copyright or to violate any federal, state or local law or regulation.

ACTIV-8, BILT-PLATES, DARVAN, DIXIE CLAY, NYTAL, PEERLESS, PYRAX, RHEOTOL, VANCIDE, VANCOR, VANCOTE, VAN GEL, VANSIL, VANTALC, VANZAN, VEECOTE and VEEGUM are registered trademarks of R.T. Vanderbilt Company, Inc.

rev08/07

