



R. T. Vanderbilt Company, Inc.

INDUSTRIAL MINERALS AND CHEMICALS

30 WINFIELD STREET, P.O. BOX 5150. NORWALK, CONNECTICUT 06856-5150 • (203) 853-1400
Fax (203) 853-1452 • Internet Address: www.rtvanderbilt.com

Specification

NYTAL® 6600

February 21, 2003

RTV Product Code: **30909**
Composition: Hydrous calcium magnesium silicate mineral mixture
Physical State: White powder

	<u>Specification</u>	<u>Test Method</u>
*Color in Oil	55 minimum	T-950
*Consistency, KU	80-125	T-1012
*Hegman Fineness, 3 lbs/gal	5.5 minimum	T-1013

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Density at 25°C	2.85 Mg/m ³
Fineness, retained on 325 mesh	nil
Moisture Content	0.6%
Oil Absorption, Rub-Out	38
pH, 10% Slurry	9.5
G.E. Brightness	92
Volume Displacement	23.7 lbs/gal
Conforms to ASTM D-605; MIL-P-15173A, Type A; 52-MA-523b, Type II	

*Certified Property

Uses - NYTAL 6600 is an ultra fine talc pigment. Suggested for use in paints where high Hegman fineness and film smoothness are required, such as semi-gloss paints. Also as filler and extender for natural and synthetic rubbers in specialized applications.

Standard Container - 50 pound paper bag