



R. T. Vanderbilt Company, Inc.

INDUSTRIAL MINERALS AND CHEMICALS

30 WINFIELD STREET, P.O. BOX 5150. NORWALK, CONNECTICUT 06856-5150 • (203) 853-1400
Fax (203) 853-1452 • Internet Address: www.rtvanderbilt.com

Specification

NYTAL® 300

May 13, 1998

RTV Product Code: **31101**
Composition: Hydrous calcium magnesium silicate mineral mixture
Physical State: White powder

	<u>Specification</u>	<u>Test Method</u>
*Color in Oil	55 minimum	T-950
*Consistency, KU	72-77	T-951
*Fineness, retained on 325 mesh	0.08% maximum	T-944
*Hegman Fineness, 3 lbs/gal	3.5 minimum	T-953

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Density at 25°C	2.85 Mg/m ³
Moisture Content at 105°C	0.6%
Oil Absorption, Rub-out	29
pH, 10% Slurry	9.4
Volume Displacement	23.7 lbs/gal
Wratten Brightness	90

Conforms to ASTM D-605; MIL-P-15173A, Type B; 52-MA-523b, Type 1.

*Certified Property

Uses - Interior wall paints, exterior house paints, primers, maintenance paints, and traffic paints. Filler for NR, synthetic rubbers, polyolefins and other polymers in specialized applications.

Standard Container - 50 pound paper bag