



# R. T. Vanderbilt Company, Inc.

INDUSTRIAL MINERALS AND CHEMICALS

30 WINFIELD STREET, P.O. BOX 5150. NORWALK, CONNECTICUT 06856-5150 • (203) 853-1400  
Fax (203) 853-1452 • Internet Address: www.rtvanderbilt.com

# Specification

## PYRAX® RG 200

August 30, 2001

RTV Product Code: **33804**  
Composition: Hydrated aluminum silicate, pyrophyllite  
Physical State: Gray to buff powder

	<u>Specification</u>	<u>Test Method</u>
*Brightness, Fired	60 minimum	T-898
*Shrinkage	2% maximum	T-897
*Fineness, retained on 200 mesh	1.0% maximum	T-706A

### GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Density at 25°C	2.8-2.9 Mg/m <sup>3</sup>
Moisture Content	0.5% maximum

\*Certified Property

*Uses - A Valuable refractory raw material for use in:*

- 1) *Insulating firebrick,*
- 2) *Metal pouring refractories,*
- 3) *Alumina-silica monolithic refractories (Ramming, gunning, and castable mixes)*
- 4) *Kiln car refractories, and*
- 5) *Foundry washes.*

Standard Container – 50 pound paper bag