



R. T. Vanderbilt Company, Inc.

INDUSTRIAL MINERALS AND CHEMICALS

30 WINFIELD STREET, P.O. BOX 5150. NORWALK, CONNECTICUT 06856-5150 • (203) 853-1400
Fax (203) 853-1452 • Internet Address: www.rtvanderbilt.com

Specification

DIXIE CLAY®

June 26, 2007

RTV Product Code: **08903**
Composition: Hydrated aluminum silicate, kaolin
Description: White to cream powder

	<u>Specification</u>	<u>Test Method</u>
*Fineness, retained on 325 mesh	0.7% maximum	T-938
*Moisture Content	1.0% maximum	T-936

GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

Brightness	70
Density at 25°C	2.6 Mg/m ³
Loss on Ignition	14%
Median Particle Size	0.2 µm
Oil Absorption, Rub-Out	42

*Certified Property

Uses - Reinforcing filler and extender for all elastomers and latexes. Used as a filler in non-black stocks and as an extender in black stocks. Reinforces and stiffens uncured and cured stocks. Controls Shrinkage in adhesive compounds. Used in coatings, primers, crack fillers and caulking compounds.

DIXIE CLAY is a registered trademark of R. T. Vanderbilt Company Inc.