R.T. Vanderbilt Company, Inc.
INDUSTRIAL MINERALS AND CHEMICALS

30 WINFIELD STREET, P.O. BOX 5150. NORWALK, CONNECTICUT 06856-5150 • (203) 853-1400
Fax (203) 853-1452 • Internet Address: www.rtvanderbilt.com

# Specification

**"TENTATIVE"**

## VANFRE® DFL

April 14, 1999

RTV Product Code: **49806**
Composition: Buffered phosphate ester solution
Physical State: Liquid

| | Specification | Test Method |
|---|---|---|
| *Color, Gardner | 7 maximum | T-73 |
| *pH | 7.2-7.8 | T-19 |
| *Solids, 2 hrs. at 105°C | 44.0-48.0% | T-2 |
| *Viscosity, Brookfield at 25°C, spindle #1 at 12 rpm | 1200 cps maximum | T-227 |

## GENERAL INFORMATION

Typical values not routinely measured or reported on the Certificate of Analysis.

| | |
|---|---|
| Density at 25°C | 1.08 $Mg/m^3$ |

*Certified Property

*Uses - Mold lubricant. Inhibits corrosion of molds and dryer flights. Prevents mold buildup.*

Standard Container - 441 pound metal drum

The information presented herein, while not guaranteed, was prepared by technical personnel and, to the best of our knowledge and belief, is true and accurate as of the date hereof. No warranty, representation or guarantee, express or implied, is made regarding accuracy, performance, stability, reliability or use. This information is not intended to be all –inclusive, because the manner and conditions of use, handling, storage and other factors may involve other or additional safety or performance considerations. The user is responsible for determining the suitability of any material for a specific purpose and for adopting such safety precautions as may be required. R.T. Vanderbilt Company does not warrant the results to be obtained in using any material, and disclaims all liability with respect to the use, handling or further processing of any such material. No suggestion for use is intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patent or to violate any federal, state or local law or regulation.